



# The Poynt P61B

## Specifications

### Processor

Application processor: Quad-core ARM Cortex A53  
Security processor: Single-core ARM Cortex M3

### Memory/storage

1GB DDR RAM/8GB Flash

### Display

7.0" touchscreen display - 800(w) x 1280(h) pixels 4.3"  
secure touchscreen display - 800(w) x 480(h) pixels  
simultaneous 10 finger capacitive multitouch

### Operating system

Poynt OS

### Connectivity

WiFi: 802.11 a/b/g/n dual channel 2.4, 5 GHz operation  
Bluetooth 4.2  
Optional features: 4G LTE cellular modems  
dual USB 2.0 ports (via optional dock)  
Ethernet: 10/100 (via optional dock)

### Camera

Front camera: 5MP with autofocus (7cm to infinity)  
Back camera: 2MP

### Audio/microphone

Stereo speaker  
Built-in microphone

### Printer

Built in 2" thermal printer  
Integrated thermal printer with graphics capabilities  
≥ 80mm/s 18+ lines per second  
Accommodates standard roll paper of 58mm (2.25in.)  
width x 25mm (1.0in.) diameter, single ply - 3 rolls  
included in box (6M/20ft. each)

### Physical

120.7mm x 250.5mm x 91.4mm | 0.7 kg

### Card reader

Hybrid MSR/Chip Reader  
Magnetic stripe reader: Triple track (tracks 1, 2, 3),  
high coercivity, bi-directional  
Chip reader: ISO 7816, 1.8V, 3V, 5V;  
synchronous and asynchronous cards;  
EMV Level 1 and 2 Type approved

### Protocols

Supports major NFC/contactless schemes,  
ISO 14443 A&B, MiFare® capable, ISO18092 capable

### Packed applications

Poynt Terminal, Poynt Register, Settlement, Help

### Other features

3-axis accelerometer, gyroscope, and compass  
Switchable full-scale ranges (≥ 5 ranges)

### Security

PCI PTS PED and Secure Reading and Exchange of Data  
(SRED) v4.x, End-to-end encryption Support TLS 1.2

### Certification

EMVCo L1 and L2 certification, FCC, IC, and CE

### Power

Battery: 2000mAh, 8.4 V  
Power Adaptor: Input 100 - 240 VAC, 50/60 Hz,  
1.5 A | Output 12V/3.33A

### Voltage

AC input 100 - 240 VAC, 50/60 Hz; DC output 12V/3.33A

### Environmental

Operation 0° to 40°C, 90% Maximum non-condensing  
up to 45°C Storage: -20°C to 75°C, 90% Maximum  
non-condensing up to 60°C

**We make it possible. You make it happen.**

UK 📞 0800 028 1662

✉️ salesuk@elavon.com

🏠 elavon.co.uk

IRE 📞 1800 995 085

✉️ sales@elavon.com

🏠 elavon.ie

© 2019 Elavon. All Rights Reserved. Poynt Logo is trademark of Poynt. All Pictures shown are for illustration purpose only. Actual product may vary due to product enhancement.

Elavon Financial Services DAC, trading as Elavon Merchant Services, is regulated by the Central Bank of Ireland.

Elavon Financial Services DAC, trading as Elavon Merchant Services, is authorised and regulated by the Central Bank of Ireland. Authorised by the Prudential Regulation Authority and with deemed variation of permission. Subject to regulation by the Financial Conduct Authority and limited regulation by the Prudential Regulation Authority. Details of the Temporary Permissions Regime, which allows EEA-based firms to operate in the UK for a limited period while seeking full authorisation, are available on the Financial Conduct Authority's website. Y4002\_3232v40221